

Electronic Hinge Preparations



Standards As Tough As Steel.™ © 2019 Steel Door Institute STEEL DOOR INSTITUTE 30200 DETROIT ROAD · CLEVELAND, OHIO 44145

Electronic Hinge Preparations

1 Purpose

It is the intention of this document to furnish users of standard steel frames with practical information regarding an acceptable method for preparing frames for 4-1/2", 5" or continuous electric hinges. This document will allow frame manufacturers to provide frames prior to having knowledge of the specific electric hinge being used.

2 Scope

The information contained herein pertains to frames manufactured in accordance with ANSI/SDI A250.8. The preparation as defined herein will accommodate the majority of electric hinges sold. It is the responsibility of the hardware specifier to assure compatible hinges are used.

3 Reference Documents

ANSI/SDI A250.6 Recommended Practice for Hardware Reinforcings on Standard Steel Doors and Frames

ANSI/SDI A250.8 SDI 100 Specifications for Standard Steel Doors & Frames

ANSI/BHMA A156.7 Template Hinge Dimensions

ANSI/BHMA A156.115 Hardware Preparation in Steel Doors and Steel Frames

4 Tolerances

All values which do not carry specific tolerances or are not marked maximum or minimum shall have the following tolerances: Linear dimensions shall be $\pm 1/16$ in. (1.6 mm). Weight or force shall be $\pm 2\%$. Angles shall be ± 2 degrees. Where only minus tolerances are given, the dimensions are permitted to be exceeded at the option of the manufacturers.

5 Location


The preparation for electric hinges is intended to be non-load bearing. Therefore it shall be located in the center hinge preparation on frames with $1-\frac{1}{2}$ pair of hinges, and on the second hinge from the bottom on frames with 2 pair of hinges.

6 Hinge Reinforcement

The hinge reinforcement shall comply with ANSI/SDI A250.6 and ANSI/SDI A250.8, and shall incorporate cutouts as shown in Figures 1, 2, 3 and 4.

7 Junction Box


A junction box may be provided to facilitate wiring and connector installation. In addition, a hole shall be provided at the top and bottom of the junction box to facilitate conduit (see Figure 4). It is the responsibility of the electrical contractor to plug any unused holes.



- Note 1: The hinge backset on the door varies by hollow metal door manufactures from $\frac{3}{16}$ to $\frac{1}{4}$ "
- Note 2: The hinge backset on the frame varies by hollow metal frame manufactures from 5/16" to 3/8"
- Note 3: Extra holes may occur in the reinforcement for tooling and installation fixturing.
- **Note 4:** Some manufacturers offer a removable feature (e.g. wire, shim, standoff projection) to allow conversion of a standard weight preparation for use with heavy weight hinge butt.
- Note 5: The most common mortise depths are in accordance with ANSI/BHMA A156.1 as follows:

Standard Weight butt 0.146" Heavy weight butt 0.190"


Figure 1 – Preparation of 1 ¾" Steel Doors & Frames for 5" Full Mortise Electric Hinge



- Note 1: The hinge backset on the door varies by hollow metal door manufactures from 3/16" to 1/4"
- Note 2: The hinge backset on the frame varies by hollow metal frame manufactures from 5/16" to 3/8"
- Note 3: Extra holes may occur in the reinforcement for tooling and installation fixturing.
- **Note 4:** Some manufacturers offer a removable feature (e.g. wire, shim, standoff projection) to allow conversion of a standard weight preparation for use with heavy weight hinge butt.
- Note 5: The most common mortise depths are in accordance with ANSI/BHMA A156.1 as follows:

Standard Weight butt 0.134" Heavy weight butt 0.180"

Figure 2 – Preparation of 1 3/4" Steel Doors & Frames for 4 1/2" Full Mortise Electric Hinge



- **Note 1:** The hinge backset on the door varies by hollow metal door manufactures from 3/16" to 1/4" when hinge filler is in place.
- Note 2: The hinge backset on the frame varies by hollow metal frame manufactures from 5/16" to 3/8"
- Note 3: Extra holes may occur in the reinforcement for tooling and installation fixturing.
- **Note 4:** Some manufacturers offer a removable feature (e.g. wire, shim, standoff projection) to allow conversion of a standard weight preparation for use with heavy weight hinge butt.
- Note 5: The most common mortise depths are in accordance with ANSI/BHMA A156.1 as follows:

Standard Weight butt 0.134" Heavy weight butt 0.180"






Figure 4 – Electrified Continuous Hinge Preparation on Standard Steel Frame

AVAILABLE PUBLICATIONS

Specifications

Specifications	
ANSI/SDI A250.6	Recommended Practice for Hardware Reinforcing on Standard Steel Doors and Frames
ANSI/SDI A250.8	Specifications for Standard Steel Doors and Frames (SDI-100)
SDI-108	Recommended Selection & Usage Guide for Standard Steel Doors
SDI-118	Basic Fire Door, Fire Door Frame, Transom/Sidelight Frame, and Window Frame Requirements
SDI-128	Guidelines for Acoustical Performance of Standard Steel Doors and Frames
SDI-129	Hinge and Strike Spacing
SDI-133	Guideline for Specifying Steel Doors & Frames for Blast Resistance
SDI-136	Guideline for Specifying Windstorm Products
Test Procedures	
ANSI/SDI A250.3	Test Procedure & Acceptance Criteria for Factory Applied Finish Coatings for Steel Doors and Frames
ANSI/SDI A250.4	Test Procedure & Acceptance Criteria for Physical Endurance for Steel Doors, Frames and Frame Anchors
ANSI/SDI A250.10	Test Procedure & Acceptance Criteria for Prime Painted Steel Surfaces for Steel Doors and Frames
ANSI/SDI A250.13	Testing and Rating of Severe Windstorm Resistant Components for Swinging Door Assemblies for Protection of Building Envelopes (Not applicable for FEMA 320/361 or ICC-500 Shelters)
SDI-113	Standard Practice for Determining the Steady-State Thermal Transmittance of Steel Door and Frame Assemblies
SDI-131	Accelerated Physical Endurance Test Procedure for Steel Doors
Construction Det	ails
ANSI/SDI A250.11	Recommended Erection Instructions for Steel Frames
SDI-110	Standard Steel Doors & Frames for Modular Masonry Construction
SDI-111	Recommended Details for Standard Steel Doors, Frames, Accessories and Related Components
SDI-122	Installation Troubleshooting Guide for Standard Steel Doors & Frames
Miscellaneous Do	ocuments
SDI-112	Zinc-Coated (Galvanized/Galvannealed) Standard Steel Doors and Frames
SDI-117	Manufacturing Tolerances for Standard Steel Doors and Frames
SDI-124	Maintenance of Standard Steel Doors & Frames
SDI-127	Industry Alert Series (A-L)
SDI-130	Electronic Hinge Preparations
SDI-134	Glossary of Terms for Hollow Metal Doors and Frames
SDI-135	Guidelines to Measure for Replacement Doors in Existing Frame Openings



STEEL DOOR INSTITUTE

30200 DETROIT ROAD • CLEVELAND, OHIO 44145 440.899.0010 • www.steeldoor.org

MEMBERS OF THE STEEL DOOR INSTITUTE

CECO

AN ASSA ABLOY DOOR GROUP COMPANY **Telecom Drive** n, TN 38358-3425) 686-8345 .cecodoor.com

RIES

ASSA ABLOY DOOR GROUP COMPANY 12th Street, P.O. Box 1648 on City, IA 50402-1648) 423-1334 .curries.com

ANSTEEL MANUFACTURING CO.

S. Flores Street Antonio, TX 78204-1406 226-8271 .deansteel.com

LA FONTAINE INDUSTRIES, INC.

ormac Road urn. MA 01801) 932-8663 . .delafontaine.com

Redwood Avenue ana, CA 92336-1638) 770-5700 .dcihollowmetal.com

LOW METAL XPRESS (HMX)

Stanwood Boulevard tsville, AL 35811-9021) 851-6670 . HMXpress.com

SKER DOOR Stanwood Boulevard

tsville. AL 35811-9021) 851-6670 .meskerdoor.com

North Hills Road oin, KY 40701) 523-0173 v.metalproductsinc.com

NEER INDUSTRIES, INC.

ASSA ABLOY DOOR GROUP COMPANY Kero Road stadt, NJ 07072 933-1900 .pioneerindustries.com

MIER STEEL DOORS & FRAMES Sterlington Road

roe, LA 71203) 361-0796 .trustpremier.com

PUBLIC DOORS & FRAMES

Republic Drive enzie, TN 38201-0580) 352-3383 v.republicdoor.com

ELCRAFT 9017 Blue Ash Road Cincinnati, OH 45242 (513) 745-6400

www.steelcraft.com

STILES AN ASSA ABLOY DOOR GROUP COMPANY 1885 Kinser Road Ceres, CA 95307 (209) 538-3667 www.stilesdoors.com

Standards As Tough As Steel.™ 1/1/2023